

PMXTREME®

OPTIMAL STYLE IN SAFETY EYEWEAR



Part	Lens
SB6310SPC••	<input type="checkbox"/> Clear
SB6310STPC••	<input type="checkbox"/> Clear Anti-Fog
SB6320SPC••	<input type="checkbox"/> Gray
SB6375SPC••	<input type="checkbox"/> Blue Mirror

- Built-in rubber nose piece provides all day comfort.
- Includes black lanyard cord for extra security while wearing.
- Rubber temple tips keep eyewear secure for the active worker.
- Extreme style in safety eyewear, with clean lines and sports appeal.
- Ventilated, straight-back flexible temples provide cool, pressure-free fit.
- Scratch resistant polycarbonate lenses provide maximum vision protection, filter out 99% of harmful UV rays.

GENERAL SPECIFICATION
Bridge: 14mm
Lens Base: 8 Curve
Lens Size Diagonal: 78mm
Lens Size Vertical: 46mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 103mm
Overall Width (Hinge-Hinge): 140mm
PD: 72mm
Weight: 26gm





PMXTREME®

OPTIMAL STYLE IN SAFETY EYEWEAR

PACKAGING

Polybag: 1pc
 Inner Box: 12 pcs
 Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, molded lens attached to the frame
Frame	Nylon	Half Frame
Nose Piece	Rubber	N/A
Sleeve (on temples)	Hard Rubber	N/A
Temple	Nylon	N/A
Hinge Screw	Nickel Silver	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB6310SPC	 Clear	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB6310STPC	 Clear Anti-Fog	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB6320SPC	 Gray	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB6375SPC	 Blue Mirror	P + L3	P Z87 + 1.5 / P c SEI CAN/CSA Z94.3-07

LENS MARKING**Symbols:**

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose
 W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 +1.5, 2.0: Rx
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices